



|                       |                                |
|-----------------------|--------------------------------|
| Beam Angle (degree)   | 60                             |
| Luminous Flux (Lumen) | 3300lm                         |
| Lumen per watt        | 110                            |
| Power factor          | >0.90                          |
| Unified Glare Rating  | < 19 - for offices and schools |
| Optical Cover         | PC (Polycarbonate)             |
| Product Type Category | LED Downlight                  |

## Fixture Information

|                        |                             |
|------------------------|-----------------------------|
| Mounting Method        | Surface                     |
| Cut out (mm)           | 160                         |
| IP-Rating              | IP65                        |
| Impact Protection (IK) | IK06 - 1 joule              |
| Operating Temperature  | -20 to +40                  |
| Housing                | Aluminium                   |
| Colour of the Fixture  | White                       |
| Colour of material     | White                       |
| Fixture Connection     | Terminal, 3-Pole (L, N, PE) |
| Series                 | DOWNLIGHT SURFACE IP65      |

## Dimensions

|               |     |
|---------------|-----|
| Height (mm)   | 110 |
| Diameter (mm) | 160 |

 **Sensor Information** Order from the **largest lighting specialist** in Europe  **Customised** quotation

Type of sensor



Up to **7 years warranty**

No Sensor



**Easy** return process